



CERBERUS

— CAMERA SYSTEM —



HD1200

Image Sensor	2/3" CMOS (viimagic 9215) with Rolling Shutter 2048x1148 total pixel, 16 : 9
Readout	1920x1080 @ 60 frames/s
Dynamic Range	linear mode: 60 dB hdr mode: up to 120 dB
Sensitivity	F 11/2000 lx at nominal gain
S/N Ratio	56 dB (Y) at nominal gain
Frame Rates	<i>in DDS mode</i> 1080p/720p 23,98/24/25/29,96/30 <i>in CDS mode</i> 1080p/720p 48/59,94/60

Introducing the *Cerberus* camera system, *LMP Lux Media Plan* continues the everlasting reinvention of the worlds smallest true HD camera systems.

Based on the successful *HD1200* camera system, the modular *Cerberus* system combines three 2/3" sensors using the identical processing hardware, making the camera heads interchangeable. Focussing on the individual advantages of different sensor types, the *Cerberus* system adapts to your needs with ground-breaking performance in every field. Experience the familiar workflow deduced with exceptional new features.

LMP
Lux Media Plan
|

What the system shares

Although each of the camera heads inhabits several individual features, the successful signal processing algorithms of our well introduced *HD1200* camera system form the fundamental basis of the *Cerberus* camera system. Combining an outstanding number of simultaneous live outputs, such as RAW, HDSDI and analog component, with the familiar camera control workflow, the *Cerberus* system perfectly adapts to your specific needs.

physically

Dimensions	camera head: 38x44x48 mm CCU: 140x120x30 mm
Weight	camera head: 140g CCU: 420g light version: 310g
Lens Mount	C-Mount adjustable back-focus, adaptors for B4, Nikon, Arri PL
Power	8-15V DC, 15Watt

technically

Format	16 : 9
Image direction	horizontal/vertical flip without latency
Output Signals	HDSDI interlaced (2x BNC) HDSDI Dual Link progressive, SDI, CVBS, analog component or Y/B-Y/R-Y interlaced, HDSDI RAW Data in 12/10 bit WeissCam or Cineform DFX HDMI (1x Mini-HDMI)
HDMI Out	camera picture in output format, or multiplexed line-by-line with second camera in 3D mode
Cable length	up to 40m with single coax cable (4mm Belden 1865A)
data format <small>between Head & CCU</small>	LMP Multiplex containing Power 12V DC / 2,7Gbit Sensor Data / bi-directional RS232
Genlock	tri-level sync +/- 2 lines in steps of 1 pixel HDSDI pixel by pixel in 3D mode

control-wise

White Balance	automatic or manual YRGB preset 3200°/5600°/7200°
Gamma	manual YRGB
Black Balance	manual YRGB
Saturation	0 to 120 %, nominal 75%
Gain	0dB, +3dB, +6dB, +12dB
Color Matrix	4 presets / 2 user defined
Detail	separate horizontal and vertical detail
Shutter	5 steps up to 1/1000 auto shutter with adjustable exposure
Test signals	8 HD test patterns
SD Format	according to HD framerate
Iris control	speed and direction
Focus control	speed and direction
Serial control	duplex / simplex RS 485 duplex / simplex RS 232 USB 2.0 / TTL 1 MBaud
Remote Control	hardware remote panel Windows GUI
System calibration	automatic black/shading/ FPN correction
3D Controls	mix- /multiplexing between camera and HDSDI genlock
Presets	4 presets of main controls

CERBERUS ELEMENTS

Several additional *Elements* are available to completely customize your *Cerberus* camera system. The motorized lens drive, the hardware remote control and the fully motorized 3D rig perfectly align with the high standards of the *Cerberus* system.



3D RIG

CONTROL

LMP – Lux Media Plan – is a leading supplier of innovative serial digital solutions. Since 1986, the German-based company has been developing standardized and custom-made applications for notable clients in Europe, the United States, Asia and the Middle East.

Over 30 years of experience in motion picture production have rendered LMP a most insightful and versatile partner for sophisticated TV, video and audio productions. LMP's high-quality solutions meet the individual requirements of a broad spectrum of clients including broadcasting corporations, film and TV productions, R&D departments of universities and companies active in medicine, aviation or security. The range of products comprises customized devices as well as proprietary developments and single items manufactured to specification.

LMP
Lux Media Plan

Platter Straße 168a
D-65193 Wiesbaden
Germany

www.luxmediaplan.de
www.crbrs.de

info@luxmediaplan.de
Tel: +49 611 531779 0